



Technical Specifications

▪ Engine Type	Air-cooled, 4-stroke, V-twin, Vertical shaft, OHV
▪ Max. power	11.3 kW (15.1 hp) / 3600 rpm
▪ Oil capacity (litres)	2.0 litres
▪ Number of cylinders	2
▪ Displacement	603cm ³
▪ Dimensions (L x W x H) (mm)	468 x 429 x 544
▪ Bore x stroke	73 x 72 mm
▪ Fuel tank capacity (litres)	
▪ Max. torque	39.1 Nm (28.8 ft.lbs) / 2200 rpm
▪ Dry weight	40.7 Kg

Type

- 4 Stroke
- Air Cooled
- V Twin
- Overhead valve
- Vertical Shaft

Features

- Single stage canister air filter
- High performance lubrication system
- Cast iron cylinder liners
- Internally vented carburetor with fuel shut-off solenoid
- Automatic compression release
- Metal engine cover
- 90 degree V-twin
- Electronic spark ignition
- Spherical combustion chamber
- Clean-out ports
- Heavy duty shift type starter
- Overhead V-valves
- Rotating grass screen

Options

- Shaft variations
- Various speed control system
- 13 or 20 Amp charge coil
- Various oil drains

Performance curves

The power rating of this engine is the Net power rating tested on a production engine and measured in accordance with SAE J1349. Actual power output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



