



## Technical Specifications

▪ <b>Engine Type</b>	Air-cooled, 4-stroke, V-twin, Vertical shaft, OHV
▪ <b>Max. power</b>	16.6 kW (22.2 hp) / 3600 rpm
▪ <b>Oil capacity (litres)</b>	2.0 litres
▪ <b>Number of cylinders</b>	2
▪ <b>Displacement</b>	726cm <sup>3</sup>
▪ <b>Dimensions (L x W x H) (mm)</b>	479 x 462 x 565
▪ <b>Bore x stroke</b>	78 x 76 mm
▪ <b>Fuel tank capacity (litres)</b>	
▪ <b>Max. torque</b>	54.3 Nm (40.0 ft.lbs) / 2000 rpm
▪ <b>Dry weight</b>	46.0 Kg

## Type

- 4 Stroke
- Air Cooled
- V Twin
- Overhead valve
- Vertical Shaft

## Features

- High performance lubrication system
- Cast iron cylinder liners
- Automatic compression release
- Dual stage canister air filter
- Metal engine cover
- 90 degree V-twin
- Electronic spark ignition
- Twin barrel, internally vented carburetor with fuel shut-off solenoid
- Spherical combustion chamber
- Clean-out ports
- Heavy duty shift type starter
- Overhead V-valves
- Rotating grass screen

## Options

- Shaft variations
- Various speed control system
- 13 or 20 Amp charge coil
- Various oil drains

## Performance curves

The power rating of this engine is the Net power rating tested on a production engine and measured in accordance with SAE J1349. Actual power output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



